



煤氣商用熱水爐 即熱恆溫式

Commercial Gas Hot Water Heater
Instantaneous Temperature-modulated Type



BRJW350HFE

熱水量大

High capacity

水溫穩定

Stable water temperature

清洗容易

Easy cleaning



BRJW350BFE

水滾茶靚

Hot water for rich tea

高溫消毒

High temperature sterilization

快速補給

Rapid recovery rate



煤氣
Towngas



煤氣商用熱水爐

Commercial Gas Hot Water Heater Instantaneous Temperature-modulated Type

BRJW350HFE

熱水量大 High capacity

以來水攝氏 25°C 計算，BRJW350HFE 熱水爐每分鐘可供應10公升60°C 熱水。
Incoming water at 25 °C, BRJW350HFE water heater is capable of supplying up to 10 litres hot water at 60 °C per minute.

水溫穩定 Stable water temperature

配備自動恆溫控制器，保持出水溫度穩定。

Equipped with an automatic temperature-modulation sensor for a stable water temperature.

清洗容易 Easy cleaning

熱水爐配備可重複使用的空氣過濾網，移除方法簡易，方便清洗。

Water heater equipped with washable & reusable air filter which is easy for removal and cleaning.

BRJW350BFE

水滾茶靚 Hot water for rich tea

配合滾水茶爐，可提供溫度高達 96°C 之滾水，即開即有，確保茶味更香更濃。

Equipped with tea boiler, boiling water up to 96°C is perfect for making great tasting tea.

高溫消毒 High temperature sterilization

BRJW350BFE 熱水爐源源不絕提供攝氏 80°C 熱水，有效以高溫消滅細菌。

BRJW350BFE water heater provides hot water at 80°C continuously for sterilization.

快速補給 Rapid recovery rate

迅速將水加熱補給，節省能源。

Reheating the water in a short period of time which saves energy.



自動電子點火
Auto Ignition



防漏熄火安全裝置
Flame Failure Device

Model no. 型號			BRJW350BFE	BRJW350HFE
尺寸 Overall Dimension	毫米 mm	高 x 闊 x 深 H x W x D	538 x 350 x 170	
重量 (公斤) Weight (kg)			16	
用氣量 Gas Consumption	兆焦耳/小時 (千瓦) MJ/hr (kW)		126 (35)	
熱水量 (公升/分鐘) Hot Water Supply (litre/min) [來水溫度 Incoming water temperature: 25 °C]	在 60°C 熱水輸出 At 60°C Output Temperature		—	10
	在 80°C 熱水輸出 At 80°C Output Temperature		5.5	—
最高熱水溫度 Maximum Hot Water Temperature	攝氏 °C		80	60
操作水壓 Operating Water Pressure	千帕 (磅/平方吋) kPa (p.s.i.)		200 (29)	
排氣方式 Flue Type			機動排氣密封式 Fan-Assisted Room Sealed	
抽氣量要求 (只適用於中央抽氣系統)* Draught Requirement (for common flue connection)*	立方米/小時 m³/hr		70	
喉管駁口 Pipe Connection	煤氣駁口 (英吋) Gas Connection (inch)		3/4" B.S.P.	
	冷水駁口 (英吋) Cold Water Connection (inch)		1/2" B.S.P.	
	熱水駁口 (英吋) Hot Water Connection (inch)		1/2" B.S.P.	
電力供應 Power Supply			AC 220V/50Hz/0.06kW	



BRJW350HFE



BRJW350BFE

注意：

此爐具必須由註冊氣體裝置技工安裝及維修。
建議為爐具進行每年最少一次的安全檢查。

Note:

Installation and service of the appliance shall be performed by registered gas installer.
We recommend a safety inspection at least once a year.

* 排氣喉與中央抽氣系統之接駁需有-125帕的壓力 The connection between flue pipe and mechanical exhaust system requires a pressure of -125Pa

1 年包零件免費保養
year warranty including parts

免費喉管設計
Free piping design

免費估價
Free cost estimation

可協助客戶向環境保護署申請使用有關裝置
Customers may be given help to apply for EPD approval



工商業查詢熱線
C & I enquiry hotline
網上客戶中心
Virtual customer centre

2963 3300

www.towngas.com

香港中華煤氣有限公司
The Hong Kong and China Gas Company Limited